






SLING CHAINS* | GRADE 10, COMPLETELY ASSEMBLED

SINGLE STRAND					DOUBLE STRAND				
									
Load bearing capacity t at tilt angle	Chain nominal thickness	1GK10-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**	Load bearing capacity t at tilt angle	Chain nominal thickness	2GK10-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**
90°	Ø mm	Order No.	Order No.	Order No.	0 - 45° 45 - 60°	Ø mm	Order No.	Order No.	Order No.
1.400	6	A01364	A01370	A01376	2.000 1.400	6	A01382	A01388	A01394
2.500	8	A01365	A01371	A01377	3.550 2.500	8	A01383	A01389	A01395
4.000	10	A01366	A01372	A01378	5.600 4.000	10	A01384	A01390	A01396
6.700	13	A01367	A01373	A01379	9.400 6.700	13	A01385	A01391	A01397
10.000	16	A01368	A01374	A01380	14.000 10.000	16	A01386	A01392	A01398
TRIPLE STRAND					QUADRUPLE STRAND				
									
Load bearing capacity t at tilt angle	Chain nominal thickness	3GK10-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**	Load bearing capacity t at tilt angle	Chain nominal thickness	4GK10-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**
0 - 45° 45 - 60°	Ø mm	Order No.	Order No.	Order No.	0 - 45° 45 - 60°	Ø mm	Order No.	Order No.	Order No.
3.000 2.100	6	A01400	A01406	A01412	3.000 2.100	6	A01418	A01424	A01430
5.300 3.800	8	A01401	A01407	A01413	5.300 3.800	8	A01419	A01425	A01431
8.000 6.000	10	A01402	A01408	A01414	8.000 6.000	10	A01420	A01426	A01432
14.000 10.000	13	A01403	A01409	A01415	14.000 10.000	13	A01421	A01427	A01433
21.200 15.000	16	A01404	A01410	A01416	21.200 15.000	16	A01422	A01428	A01434

* Based on DIN EN 814-4. ** Shortening, consisting of 5 chain links and shortening hook with fork head. Different dimensions or final equipment on request!
Dimension L = usable length. Please specify when ordering!