





SLING CHAINS DIN EN 818-4 | GRADE 8, COMPLETELY ASSEMBLED

SINGLE STRAND					DOUBLE STRAND						
											
Load bearing capacity t at tilt angle	Chain nominal thickness	1GK8-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand*	Load bearing capacity t at tilt angle		Chain nominal thickness	Extra length per meter	Mehrlänge pro Meter	Shortening per strand*	
					90°						0 – 45°
2.000	8	A00380	A01301	A01358	2.800	2.000	8	A00447	A01308	A02358	
3.150	10	A00381	A01302	A01359	4.250	3.150	10	A00448	A01309	A02359	
5.300	13	A00382	A01303	A01360	7.500	5.300	13	A00449	A01310	A02360	
8.000	16	A00383	A01304	A01361	11.200	8.000	16	A00450	A01311	A02361	
TRIPLE STRAND					QUADRUPLE STRAND						
											
Load bearing capacity t at tilt angle	Chain nominal thickness	3GK8-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand*	Load bearing capacity t at tilt angle		Chain nominal thickness	4GK8-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand*	
					0 – 45°	45 – 60°					0 – 45°
4.250	3	8	A00514	A01315	A03358	4.250	3.000	8	A00581	A01322	A04358
6.700	4	10	A00515	A01316	A03359	6.700	4.750	10	A00582	A01323	A04359
11.200	8	13	A00516	A01317	A03360	11.200	8.000	13	A00583	A01324	A04360
17.000	11	16	A00517	A01318	A03361	17.000	11.800	16	A00584	A01325	A04361

* Shortening, consisting of 5 chain links and shortening hook with fork head. Different dimensions or final equipment on request!
Dimension L = usable length. Please specify when ordering!