# Spring balancer / Digital crane scale





### Spring balancer 600 series

Spring balancers and balancers make the suspended load almost weightless. Work equipment and tools attached to spring balancers are quicker to pick up


and to "put back down". The suspended load remains virtually suspended when released.

This greatly improves productivity and workplace tidiness.

- Robust aluminium pressure die-cast housing
- Durable steel wire cable
- Precise cable guidance
- Various cable lengths

Serie 630

• With rope stopper and mounting snap hook



ТҮРЕ	Capacity	Rope length	Rope-Ø	Weight	Dimensions in mm						Order No.		
TIPE	kg	m	mm	kg	A	В	C	D	E	F	G	Н	
630	0.4 – 1	1.6	2	0.63	60	250	Ø6	113	93	93	Ø 8	113	G30120
631	1 – 2	1.6	2	0.67	60	250	Ø6	113	93	93	Ø 8	113	G30121
632	2 – 3	1.6	2	0.79	60	250	Ø6	113	93	93	Ø 8	113	G30122
633	2 – 4	2.5	2.5	2.85	99.5	415	Ø 10	192	162.5	162.5	Ø 10	192	G30123
634	4 - 6	2.5	2.5	3	99.5	415	Ø 10	192	162.5	162.5	Ø 10	192	G30124
635	6 – 8	2.5	2.5	3.1	99.5	415	Ø 10	192	162.5	162.5	Ø 10	192	G30125
636	8 – 10	2.5	2.5	3.2	99.5	415	Ø 10	192	162.5	162.5	Ø 10	192	G30126
637	10 – 14	2.5	2.5	3.5	99.5	415	Ø 10	192	162.5	162.5	Ø 10	192	G30127

Scan me

## Digital crane scale MCW

Digital, reliable and easy-to-use crane scales for industrial use, with standard storage or transport case. Due to the small amount of space it takes up, the MCWN series of crane scales enable lifting equipment to be used effectively. The MCWN series of crane scales come with a wireless module, a USB port for PC connection, a printer connection and a weight display as standard. A test certification performed with test weights is provided with each set of crane scales.

#### Features:

- Weighing range from 300 kg to 25.000 kg
- Large 25 mm LCD display, backlit
- Precision: +/- 0.03% of the weighing range (from limit value)
- Humidity-resistant keyboard with 5 keys: ZERO SETTING, TARE DEDUCT. (autom. or manual), MODE, PRINT and ON/OFF
- Robust, stove-enamelled steel housing
- Standard remote control covering distances of up to 8 metres. Can be configured by customer as tare deduction or as 4-key remote keyboard.
- Power supply from 4 batteries (type AA), operation approx. 40 hours (without wireless transmission).
- Digital setup and calibration, can be programmed directly with sample weight via keyboard or PC (with tools).

#### **Digital crane scale MCW**

ТҮРЕ	Weighing range kg	Digit kg	Weight approx. kg	Order No.
MCWNT1	300 / 600 / 1.500	0.1 / 0.2 / 0.5	11	F00650
MCWNT6	1.500 / 3.000 / 6.000	0.5 / 1 / 2	11	F00668
MCWNT9	3.000 / 6.000 / 9.500	1/2/5	11	F00651
MCWHU15	15.000	2	70	F00652
MCWHU25	25.000	5	70	F00653

Other crane scales or made of stainless steel on request.



- Digital filter and programmable auto-power-down function
- Operating temperature: -10/+40°C
- RS232 port with RJ45 connection for fast programming with tools
- Standard storage and transport case

#### **Options for Digital crane scale MCW**

TYPE	Description	Order No.	
GG1T5	Rotatable lower hook with safety lock 1.500 kg	F00669	
GG7	Rotatable lower hook with safety lock 7.000 kg	F00663	
GG15	Rotatable lower hook with safety lock 15.000 kg	F00664	
CA2	Connecting ring 2.500 kg	F00665	
CA8	Connecting ring 8.000 kg	F00666	
CA15	Connecting ring 15.000 kg	F00667	