

Flat webbing slings from polyester

- Manufactured in different colors with type/safety instruction labels
- For gentle load lifting
- Tonnage strips woven in
- Safety factor 7 against breaking
- Safety label with user instructions

Web slings are manufactured from 25 mm up to 300 mm width (Special sizes up to 900 mm). We offer here our most often requested sizes! They are available for a very competitive price! All slings have a protective PU impregnation and reinforced loops. Textile web slings should be used for applications where other lifting accessories like chains, steel wire or rope could cause damage to the surface of the load. Each sling has a captive, sewn on capacity label and a quality certificate including a tag for your annual safety test report. It also includes a safe use instruction label in two languages as required for product liability.



1D-240

Flat webbing slings from polyester (PES) acc. CEN EN 1492-1 with reinforced loops

TYPE	Capacity WLL (kg) / Safety factor of 7					Band width x tape thickness mm	Order No. for lengths of						
							2 m	3 m	4 m	5 m	6 m	8 m	10 m
double-layer													
1D-30	1,000	800	2,000	1,400	1,000	30 x 7	B00917	B00925	B00933	B00941	B00949	B00957	B00965
1D-60	2,000	1,600	4,000	2,800	2,000	60 x 7	B00918	B00926	B00934	B00942	B00950	B00958	B00966
1D-90	3,000	2,400	6,000	4,200	3,000	90 x 7	B00919	B00927	B00935	B00943	B00951	B00959	B00967
1D-120	4,000	3,200	8,000	5,600	4,000	120 x 7	B00920	B00928	B00936	B00944	B00952	B00960	B00968
1D-150	5,000	4,000	10,000	7,000	5,000	150 x 7	B05002	B05003	B05004	B05005	B05006	B05008	B05010
1D-180	6,000	4,800	12,000	8,400	6,000	180 x 7	–	B00930	B00938	B00946	B00954	B00962	B00970
1D-240	8,000	6,400	16,000	11,200	8,000	240 x 7	–	B00931	B00939	B00947	B00955	B00963	B00971

- **Special versions and further designs on request!**
- **PUR coatings and PUR protective sleeves on request!**

