

Sling chains*, grade 8, completely assembled

SINGLE STRAND					DOUBLE STRAND					
 Dimension L = usable length Please specify when ordering!					 Dimension L = usable length Please specify when ordering!					
Load bearing capacity kg at tilt angle	Chain nominal thick- ness	1GK8-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**	Load bearing capacity kg at tilt angle		Chain nominal thick- ness	2GK8-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**
90°	Ø mm	Order No.	Order No.	Order No.	0 to 45°	45 to 60°	Ø mm	Order No.	Order No.	Order No.
1,120	6	A01250	A01300	A01357	1,600	1,120	6	A01254	A01307	A02357
2,000	8	A00380	A01301	A01358	2,800	2,000	8	A00447	A01308	A02358
3,150	10	A00381	A01302	A01359	4,250	3,150	10	A00448	A01309	A02359
5,300	13	A00382	A01303	A01360	7,500	5,300	13	A00449	A01310	A02360
8,000	16	A00383	A01304	A01361	11,200	8,000	16	A00450	A01311	A02361

TRIPLE STRAND						QUADRUPLE STRAND							
		Dimension L = usable length Please specify when ordering!							Dimension L = usable length Please specify when ordering!				
Load bearing capacity kg at tilt angle		Chain nominal thick- ness	3GK8-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**	Load bearing capacity kg at tilt angle		Chain nominal thick- ness	4GK8-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**		
0 to 45°	45 to 60°	Ø mm	Order No.	Order No.	Order No.	0 to 45°	45 to 60°	Ø mm	Order No.	Order No.	Order No.		
2,360	1,700	6	A01262	A01314	A03357	2,360	1,700	6	A01266	A01321	A04357		
4,250	3,000	8	A00514	A01315	A03358	4,250	3,000	8	A00581	A01322	A04358		
6,700	4,750	10	A00515	A01316	A03359	6,700	4,750	10	A00582	A01323	A04359		
11,200	8,000	13	A00516	A01317	A03360	11,200	8,000	13	A00583	A01324	A04360		
17,000	11,800	16	A00517	A01318	A03361	17,000	11,800	16	A00584	A01325	A04361		

Sling chains*, grade 10, completely assembled

SINGLE STRAND					DOUBLE STRAND								
 Dimension L = usable length Please specify when ordering!								 Dimension L = usable length Please specify when ordering!					
Load bearing capacity kg at tilt angle	Chain nominal thick- ness	1GK10-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**	Load bearing capacity kg at tilt angle		Chain nominal thick- ness	2GK10-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**			
90°	Ø mm	Order No.	Order No.	Order No.	0 to 45°	45 to 60°	Ø mm	Order No.	Order No.	Order No.			
1,400	6	A01364	A01370	A01376	2,000	1,400	6	A01382	A01388	A01394			
2,500	8	A01365	A01371	A01377	3,550	2,500	8	A01383	A01389	A01395			
4,000	10	A01366	A01372	A01378	5,600	4,000	10	A01384	A01390	A01396			
6,700	13	A01367	A01373	A01379	9,400	6,700	13	A01385	A01391	A01397			
10,000	16	A01368	A01374	A01380	14,000	10,000	16	A01386	A01392	A01398			

* In accordance with DIN EN 818-4


** Shortening, consisting of 5 chain links and shortening hook with fork head. Different dimensions or final equipment on request!

Sling chains*, grade 10, completely assembled

TRIPLE STRAND						QUADRUPLE STRAND					
		Dimension L = usable length Please specify when ordering!						Dimension L = usable length Please specify when ordering!			
Load bearing capacity kg at tilt angle	Chain nominal thickness	3GK10-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**		Load bearing capacity kg at tilt angle	Chain nominal thickness	4GK10-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**	
0 to 45°	45 to 60°	Ø mm	Order No.	Order No.	Order No.	0 to 45°	45 to 60°	Ø mm	Order No.	Order No.	Order No.
3,000	2,100	6	A01400	A01406	A01412	3,000	2,100	6	A01418	A01424	A01430
5,300	3,800	8	A01401	A01407	A01413	5,300	3,800	8	A01419	A01425	A01431
8,000	6,000	10	A01402	A01408	A01414	8,000	6,000	10	A01420	A01426	A01432
14,000	10,000	13	A01403	A01409	A01415	14,000	10,000	13	A01421	A01427	A01433
21,200	15,000	16	A01404	A01410	A01416	21,200	15,000	16	A01422	A01428	A01434

Sling chains*, grade 12, completely assembled

SINGLE STRAND					DOUBLE STRAND					
		Dimension L = usable length Please specify when ordering!					Dimension L = usable length Please specify when ordering!			
Load bearing capacity kg at tilt angle	Chain nominal thick- ness	1GK12-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**	Load bearing capacity kg at tilt angle	Chain nominal thick- ness	2GK12-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**	
90°	Ø mm	Order No.	Order No.	Order No.	0 to 45°	0 to 45°	Ø mm	Order No.	Order No.	Order No.
2,360	7	A01436	A01440	A01444	3,350	2,360	7	A01448	A01452	A01456
3,000	8	A01437	A01441	A01445	4,250	3,000	8	A01449	A01453	A01457
5,000	10	A01438	A01442	A01446	7,100	5,000	10	A01450	A01454	A01458
8,000	13	A01439	A01443	A01447	11,200	8,000	13	A01451	A01455	A01459

TRIPLE STRAND						QUADRUPLE STRAND							
		Dimension L = usable length Please specify when ordering!							Dimension L = usable length Please specify when ordering!				
Load bearing capacity kg at tilt angle		Chain nominal thick- ness	3GK12-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**	Load bearing capacity kg at tilt angle		Chain nominal thick- ness	4GK12-GKH completely assembled, usable length: 1 m	Extra length per meter	Shortening per strand**		
0 to 45°	45 to 60°	Ø mm	Order No.	Order No.	Order No.	0 to 45°	45 to 60°	Ø mm	Order No.	Order No.	Order No.		
5,000	3,550	7	A01460	A01464	A01468	5,000	3,550	7	A01472	A01476	A01480		
6,300	4,500	8	A01461	A01465	A01469	6,300	4,500	8	A01473	A01477	A01481		
10,600	7,500	10	A01462	A01466	A01470	10,600	7,500	10	A01474	A01478	A01482		
17,000	11,800	13	A01463	A01467	A01471	17,000	11,800	13	A01475	A01479	A01483		

* In accordance with DIN EN 818-4

** Shortening, consisting of 5 chain links and shortening hook with fork head. Different dimensions or final equipment on request!