



# Slip winch systems

## PLANNING SHEET

# Enquiry form PLANETA slip winches

## Personal data

Name	Street		
First name	Postcode	City	
Company / Association	Country		
Phone	E-Mail		

## 1. Version and number of pieces

- ☐ electrical: \_\_\_\_\_ phases \_\_\_\_\_ Volt \_\_\_\_\_ Hz (*standard: 3Ph/400V/50Hz*)
- ☐ pneumatic: \_\_\_\_\_ l/sec \_\_\_\_\_ bar
- ☐ hydraulic: \_\_\_\_\_ l/min \_\_\_\_\_ bar
- ☐ Emergency hand crank in case of loss of power supply
- Desired quantity: \_\_\_\_\_
- Lifting/unlifting per year approx.: \_\_\_\_\_ (*standard: ~100*)

## 2. Capacity

Maximum weight including slip trolley: \_\_\_\_\_ kg

Slope of the track at the steepest point: \_\_\_\_\_ °

Length of track: \_\_\_\_\_ m

### Profile of the track:

- ☐ Rising on the entire track, slip trolley slips down automatically (*standard*)
- ☐ Track contains horizontal sections, slip trolley does not descend automatically

### Track position:

- ☐ Always in working line of winch (*standard*)
- Number of slip trolleys: \_\_\_\_\_
- ☐ Lateral deviation from the working line: \_\_\_\_\_ °
- In case of several trolleys, distance between trolleys: \_\_\_\_\_ m

### Rolling conditions of the slip trolley:

- ☐ Steel wheels, mounted, on steel rail
- ☐ Car trailer on surface:
- ☐ Concrete / pavement
- ☐ Shore, silt, grass
- ☐ Sand
- ☐ Other: \_\_\_\_\_

## 3. Slip speed

- ☐ Slow (~5 m/min)
- ☐ Fast (~15 m/min)
- ☐ Medium (~10 m/min) (*standard*)
- ☐ Variable up to \_\_\_\_\_ m/min

## 4. Equipment

- ☐ Freshwater (*standard*)
- ☐ Saltwater
- ☐ Indoor (*standard*)
- ☐ Outdoor, covered
- ☐ Outdoor, unprotected
- ☐ Consider risk of flooding / overtopping

### Height of rope drain:

- ☐ Standard
- ☐ Close to the ground
- ☐ Desired: \_\_\_\_\_ mm

### Fastening on:

- ☐ Steel profile beam (*standard*)
- ☐ Concrete floor, quality: \_\_\_\_\_

### Rope:

- ☐ Steel rope (*standard*)
- ☐ Stainless steel rope
- ☐ Plastic rope

## 5. Control and operation

- ☐ Control installed and wired on the winch
- ☐ Control for wall mounting with \_\_\_\_\_ m long connection cables (*standard: 3 m*)
- ☐ Operation Manual control button on \_\_\_\_\_ m long control cable (*standard: 3 m*)
- ☐ Radio control
- ☐ Radio control with backup control switch, pluggable
- ☐ Mains cable with CEE plug on \_\_\_\_\_ m long mains cable
- ☐ Existing operator systems to be integrated (card/chip reader)

## 6. PLANETA-Service:

- ☐ Fasteners for floor fixing
- ☐ Dimensioning of concrete anchors
- ☐ Installation
- ☐ Commissioning
- ☐ Operator training
- ☐ Service and maintenance
- ☐ Warranty extension by \_\_\_\_\_ years

Sketch of the terrain cross-section

**Do you have any questions? We will support you. Give us a call!**



### Export Director

Roland Hessels

Phone: +49 2325 9580 57

Mobil: +49 172 411 8646

roland.hessels@planeta-hebetechnik.de



**PLANETA**



**PLANETA - Hebetechnik GmbH**

Resser Straße 17  
44653 Herne  
Germany

Phone: +49 (0) 2325 9580 0  
Fax: +49 (0) 2325 77077

E-Mail: [info@planeta-hebetechnik.de](mailto:info@planeta-hebetechnik.de)  
Internet: [www.planeta-hebetechnik.de](http://www.planeta-hebetechnik.de)

