GHF 1250 K

## PUSH TROLLEY | **GHF & PHF**

Push trolley for steel girders, load capacity: up to 6,300 kg, manual movement of the manual or electric chain hoist

### GHF 500 K

- Capacity: to 500 kg
- Glass fibre reinforced plastic castors
- Optimum ease of movement
- Smooth running
- Side signs made of die-cast aluminium with fall and climbing protection
- Low weight of only 2.5 kg
- Galvanised support bolt
- Flange width 50 – 149 mm
- Minimum curve radius 1,200 mm

PHF 1250

### PHF 1250 – 6300

- Capacity:1.250 – 6.300 kg
- Castors made of grey cast iron, cylindrical for flat track supports, ball bearing mounted
- Grey cast iron side plates with fall and climbing protection
- PHF 1250/2500 with 1 support bolt
- PHF 5000/6300 with 2 support bolts
- Galvanised support bolt
- Flange width infinitely adjustable
- Optional parking brake for PHF 1250
- Optional guide rollers
- Optionally available with crowned castors
- Optional Niro-Castors*
- Optional Plastic castors*

* Load reduction

**Option: Guide castors**

| TYPE | Capacities in kg acc. ISO (FEM)* | | | | | Min. Curve radius mm | Weight kg | Flange width mm | Order No. | Flange size width mm | Order No. *** |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | A3/M3 | A4/M4 | A5/M5 | A6/M6 | A6/M6 | | | | | | |
| **GHF 500K**** | 500 | 500 | 500 | 400 | 320 | 1,200 | 2,5 | 50 - 99 | **H20729** | 100 - 149 | **H20735** |
| **PHF 1250** | 1,250 | 1,000 | 800 | 630 | 500 | 1,000 | 10 | 70 - 140 | **H20800** | 70 - 240 | **H20745** |
| **PHF 2500** | 2,500 | 2,000 | 1,600 | 1,250 | 1,000 | 1,500 | 19 | 88 - 200 | **H20801** | 88 - 300 | **H20746** |
| **PHF 5000** | 5,000 | 4,000 | 3,200 | 2,500 | 2,000 | 1,800 | 32 | 91 - 300 | **H20802** | 91 - 300 | **H20802** |
| **PHF 6300** | 6,300 | 5,000 | 4,000 | 3,200 | 2,500 | 1,800 | 47 | 91 - 300 | **H20803** | 91 - 300 | **H20803** |

**Only in conjunction with PEH 250/500 ***Bolt sets without trolley