



## TROLLEY | PHFR

Corrosion-resistant manual trolley for steel beams,  
Load capacity: up to 1,250 kg, manual movement of the  
manual or electric chain hoist

### Features:

- Load capacity: 630 - 1,250 kg
- Castors made of corrosion-resistant steel, cylindrical for flat runway beams, ball bearing mounted
- Support pins corrosion-resistant
- Side plates cataphoresis-coated, resistant to water, oils, weak alkalis and acids, with fall and climbing protection
- Flange width infinitely adjustable

### Accessories and options:

- Support rollers for cornering
- Crowned track rollers made of corrosion-resistant steel
- Plastic track rollers
- Special support pins for special flange width ranges
- Low-temperature grease for the ball bearings of the track rollers

| TYPE      | Capacity in kg according to ISO (FEM) |       |       |       |       | Min.<br>Curve radius<br>mm | Weight<br>kg | Flange<br>width<br>mm | Order No. | Flange size<br>widthmm | Order No. * |
|-----------|---------------------------------------|-------|-------|-------|-------|----------------------------|--------------|-----------------------|-----------|------------------------|-------------|
|           | A4/M4                                 | A5/M5 | A6/M6 | A7/M7 | A7/M7 |                            |              |                       |           |                        |             |
| PHFR 1250 | 630                                   | 500   | 400   | 320   | 250   | 1,000                      | 11           | 70 - 140              | H21400    | 70 - 240               | H21410      |
| PHFR 2500 | 1,250                                 | 1,000 | 800   | 630   | 500   | 1,500                      | 20           | 88 - 200              | H21401    | 88 - 300               | H21411      |

\*Bolt sets without trolley